

SCHEDA TECNICA

AS 400 INDUSTRIAL VACUUM

ASPIRATORI INDUSTRIALI PER SFRIDI, CONFEZIONAMENTO E OEM

The **AS 400 industrial vacuum** is designed to **collect** large amounts of **production trimmings**. The **Depureco's vacuum** from the **food & pharma range** is fitted with a **side-channel turbine** situated under the **215 Lt collection chamber**. **Suction**, which is from the bottom, means that the **vacuumed material** is sent straight into a **filter bag**, thus allowing a large **number of materials** to be recovered, such as paper, plastic, and packaging trimmings. The **inspection window** on the top cover of this **vacuum cleaner** allows the operator to inspect the **level of material** inside the **container**.




POTENZA
4 kW



CAPACITÀ
215 Lt

HIGHLIGHTS**SUCTION UNIT**

The suction unit is a side channel blower with direct coupling between motor and impeller. The side channel blower is equipped with a safety valve to guarantee a totally safe continuous work, without any maintenance.

**INLET**

A robust nozzle acts as the intake point for the vacuumed material. A deflector is joined to the nozzle so that the material is conveyed towards the bottom of the bag. Nozzles in different diameters are available upon request and a second one can be installed on the lid.

**FILTERING ELEMENT**

Inside the container there is a textile bag for material collection. The material passes through the inlet, and it goes into the bag. Meanwhile the air passes through the textile permitting to guarantee a continuous suction. This system forces the material to the bottom of the bag, in order to compact the residual material and collect big quantities into the bag.

**INSPECTION WINDOW**

AS vacuum cleaners are equipped with an inspection window which gives the possibility to check the quantity of material inside the bin without opening the lid.

DATI TECNICI**MOTORE**

Tipologia	side channel blower
Voltaggio	400V
IP	55
Vuoto in continuo	300mBar
Massima portata d'aria	320m3/h
Valvola di sicurezza	included
Livello di rumorosità	72dB(A)
Frequenza	50/60Hz
Potenza	5,5HP
Classe di isolamento	F

MACCHINA

Bocca aspirante	70Ø mm
Dimensioni	680 x 1.200mm
Altezza	1.370mm
Peso	100Kg

OPZIONI

ALTRE OPZIONI



BX

Contenitore in acciaio INOX AISI 304



TX

Contenitore camera e struttura in acciaio INOX AISI 304



GRD

Messa a terra

ACCESSORI



P10866

TERMINALE IN ACCIAIO Ø 70/50MM

Riduzione per innesto rapido aspiratore in acciaio zincato diametro 70/50 mm